

# MC904P

## 4G 4-Channel Mobile DVR

MC904P is a 4G MDVR that supports 4 channels of 1080p video input. It features a unique design with a 1TB SSD and supports one 512GB SD card. With its compact size, it is easy to install and transport. The device has an aluminum alloy shell, ensuring good heat dissipation. It supports emergency alarm function, 4-channel digital signal input, 1-channel digital signal output, and 2 RS232 serial ports for connecting various peripherals. Additionally, the device is equipped with built-in AI algorithms, supporting ADAS, DMS, BSD, and 360-degree video stitching. It effectively helps drivers enhance transportation safety and reduce pedestrian and vehicle accidents.



### Key Features



#### 4-CH camera

The device could supports 4 channel camera simultaneous working.



#### Multiplex input and output

Support up to 4 digital input interfaces, 1 digital output interface, 2 RS232 interfaces. External devices such as RFID reader, fuel sensors and PTZ can be integrated.



#### AI algorithm

The device supports DMS, ADAS and BSD three algorithms.



#### H.265/H.264 encode and large memory

H.265/H.264 encoding and decoding to improve the memory space utilization. Supports 1TB SSD and one 512GB SD card.



#### Built-in WIFI

WIFI can be used as WiFi Hotspot.



#### Convenient operation

Configured with a graphical menu operation interface, you can use the mouse or the remote control to configure the parameters.

## Product specifications

<b>Hardware</b>	Operation System	Linux
	CPU	ARM Cortex CA9 Dual-Core + NPU@0.7T
	Memory	1* 1TB SSD (M.2 SATA protocol) + 1*512GB SD card
	GNSS	GPS+BDS(with external G-mouse)
	G-sensor	3-axis acceleration sensor
	Speaker	✓
	Mic	✓
	Sim card	Standard sim
	LED	Red(Power),Green(GPS & 4G & WiFi & SD & HDD)
	I/O Ports	4*digital inputs, 1*digital output, 2*RS232 2*RS232 port or 1*RS485 port and 1*RS232
<b>Camera</b>	Other	1-channel voice intercom interface, which can connect the voice handle
	Video	4-CH AHD, 1.0Vp-p, 75Ω, 1080P
	ADAS	Yes
	DMS	Yes
	BSD	Yes
	Video encoding	H.264/H.265, default H.264
	Video standards	PAL, NTSC
	Video resolution	Options: 1080P/720P/D1 Total 1080P at 60 fps
<b>Network</b>	Compression format	G.711A
	MC904P-EU	FDD LTE: B1/B3/B5/B7/B8/B20/B28 TDD LTE: B38/B40/B41 WCDMA: B1/B5/B8 GSM: B3/B8
	MC904P-LA	FDD LTE: B1/B2/B3/B4/B5/B7/B8/B28/B66 TDD LTE: B40 WCDMA: B1/B2/B4/B5/B8 GSM: B2/B3/B5/B8
	MC904P-NA	FDD LTE: B2/B4/B5/B12/B13/B14/B66/B71 WCDMA: B2/B4/B5
	WIFI	2.4GHz, 802.11 b/g/n
<b>Others</b>	Protocol	JT/T808-2011, JT/T808-2019 JT/T1076-2016, JT/T1078-2016
	Power supply	DC: +9V ~ +36V
	Operation Temperature	-20°C to +70°C
	Operation Humidity	8% to 90%
	Net weight	450g
	Dimension	195mm*183mm*60mm
	Certification	CE/FCC/RoHS