



OBDII Harness 5th Gen

Install GPS trackers faster and easier with **OBDII Harness**.

OBDII Harness is used to install HCV5/LCV5 trackers to light commercial vehicles. CANbus data reading is available using OBDII harness. Connection via OBDII can be also used as a power source.

Applications

- OBD CANbus data reading

Key Features

- Faster and easier installation
- Professional installation
- Minimize risk of faulty installations

Compatibility

✓ HCV5	✓ LCV5	⊘ Pro5
--------	--------	--------

Detailed specifications

Environmental specifications

Temperature range -35 to +75 °C

Electrical specifications

Voltage range Up to 16 V DC

Physical properties

Connector type OBDII (Type B 24V, 16 pin)

CAN interfaces 1


Wire cross sectional area 0.5 mm² (20 AWG)

Cable length 1 m

Accessory wire length 0.5 m


Standard OBDII Harness Pinout

OBDII connector




Pin	Wire color	Function
1	Green/White	Single-Wire CAN
4	Black	Ground
5	Grey	AIN1
6	White/Red	CAN High
7	Brown	K-Line
16	Red	Power supply
14	Blue/Red	CAN Low

14 pin connector



Pin	Wire color	Function
1	Red	Power supply (9-32 V)
2	Purple	DOUT1
3	Green/Yellow	1-Wire data
4	Pink	DIN3
5	Yellow	DIN4
6	Blue	CAN Low
7	Brown	K-Line
8	Black	Ground
9	Orange	DOUT2
10	Red/Yellow	1-Wire power
11	Green	AIN2
12	Grey	AIN1
13	White	CAN High
14	Green/White	Single-Wire CAN

16 pin connector



Pin	Wire color	Function
1	White/Brown	RS485 line A
2	Green/Brown	Port A RS232 TX
3	Pink/Green	Port B RS232 TX
4	Yellow/Black	DIN1
5	Pink/Black	DIN2
6	White/Green	AIN4
7	Blue/Red	CAN Low
8	Black	Ground
9	Yellow/Brown	RS485 line B
10	Blue/Yellow	PortA RS232 RX
11	Red/Cyan	PortB RS232 RX
12	White/Purple	DOUT3
13	White/Orange	DOUT4
14	White/Grey	AIN3
15	White/Red	CAN High
16	Red/Yellow	1-Wire power

Ordering information

K00093

OBDII harness for installation into light vehicles

Contact information:

Perkūnkiemio g. 6
LT-12130 Vilnius, Lithuania
Phone: +370 520 451 88
Web: www.ruptela.com

Datasheet v1.4
2021-10-05