

2ch AI Dashcam

Hero-MC30-01

Super mini 1+1 ch AI dashcam for commercial fleet



Key Features

- Stylish new appearance
- Compact design, least blocking for driver view sight
- Easy installation
- Detachable 2nd camera, flexible for extension
- Cost-effective and more affordable
- Support time lapse mode
- Remote wake up by calling & text messages

Specifications

Model	Hero-MC30-01 N2
General	
OS	Embedded Linux
Language	English/Chinese (support customization)
4G	Built-in 4G module, different module option for different bands of regions
Wi-Fi	Built-in Wi-Fi module, 2.4GHz+5.8GHz Support AP mode /CPE mode. Support configuration via mobile APP Howen-itoool
Bluetooth	Built in. Bluetooth 4.2
Position	Built in. dual mode position mode: GPS+Beidou, GPS+GLONASS (optional)
G-Sensor	Built-in 6-axis G-sensor, support HA/HB/HC, Impact, Rollover
Video and Audio	
Video	Front camera: 1 ch 1080p@30fps Detachable camera: 1ch 1080p@30fps
Audio	1 ch
HFOV	Front camera: HFOV 116°
Audio in	1ch
Video Compression	H.265/H.264
Audio Format	G726, PCM
Time-lapse Recording	Support time-lapse recording after ignition off
Configure	Howen i-tool/ SMS
Microphone	Built-in
Speaker	Built-in
Storage	
External storage	Support 1 x TF, max. 1TB
Interface	
Emergency button	1 pcs, on the dashcam, color: black
Digital input	1 x button on the dashcam
RS232	1 x RS232
Power output	1 x 12 V
AI	

DMS	Eye close, Distraction, Yawning, Smoking, Phone use, DMS camera cover, Seatbelt unfastened, IR-block glasses warning Face recognition: Driver Leave/Change/Return, Driver abnormal * IR-block glasses warning needs IR DMS camera
ADAS	FCW (Forward Collision Warning) HMW (Headway Monitoring Warning) PCW (Pedestrian Collision Warning)
Power	
Power	9-36V DC
OBD power supply	Supported (option)
Sleep Mode	Supported
Environment	
Working temp	-20°C to 70°C
Storage temp	-40°C to 85°C
Structure	
Dimensions	110*67.8*29.5 mm
Weight	194g

● Dimensions



● Appearance

